
Name

rdmetadata — Tool for altering Rivendell cart metadata

Synopsis

```
rdmetadata --cart-number=cart [OPTIONS]
```

Description

rdmetadata(1) is a command-line tool for setting or altering cart metadata in the Rivendell Radio Automation System.

Options

<code>--add-schedcode=<i>schedcode</i></code>	Add scheduler code <i>schedcode</i> to <i>cart</i> . Default action is to leave the scheduler codes unaltered.
<code>--agency=<i>agency</i></code>	Set <i>cart</i> agency metadata to <i>agency</i> . Default action is to leave the agency unaltered.
<code>--album=<i>album</i></code>	Set <i>cart</i> album metadata to <i>album</i> . Default action is to leave the album unaltered.
<code>--artist=<i>artist</i></code>	Set <i>cart</i> artist metadata to <i>artist</i> . Default action is to leave the artist unaltered.
<code>--bpm=<i>bpm</i></code>	Set <i>cart</i> BPM metadata to <i>bpm</i> . Default action is to leave the BPM unaltered.
<code>--composer=<i>composer</i></code>	Set <i>cart</i> composer metadata to <i>composer</i> . Default action is to leave the composer unaltered.
<code>--conductor=<i>conductor</i></code>	Set <i>cart</i> conductor metadata to <i>conductor</i> . Default action is to leave the conductor unaltered.
<code>--label=<i>label</i></code>	Set <i>cart</i> label metadata to <i>label</i> . Default action is to leave the label unaltered.
<code>--publisher=<i>publisher</i></code>	Set <i>cart</i> publisher metadata to <i>publisher</i> . Default action is to leave the publisher unaltered.
<code>--rem-schedcode=<i>schedcode</i></code>	Remove scheduler code <i>schedcode</i> from <i>cart</i> . Default action is to leave the scheduler codes unaltered.
<code>--songid=<i>songid</i></code>	Set <i>cart</i> song ID metadata to <i>songid</i> . Default action is to leave the song ID unaltered.
<code>--title=<i>title</i></code>	Set <i>cart</i> title metadata to <i>title</i> . Default action is to leave the title unaltered.
<code>--year=<i>year</i></code>	Set <i>cart</i> year metadata to <i>year</i> . Default action is to leave the year unaltered.
<code>--verbose</code>	Print messages to STDOUT describing progress.

See Also

[rdlibrary\(1\)](#)