

---

## Name

rd\_deleteaudio — Rivendell Audio Store C Library Function

## Synopsis

```
#include <rivwebcapi/rd_deleteaudio.h>

int    RD_DeleteAudio(hostname[], username[], passwd[], ticket[],
                      cartnumber, cutnumber, user_agent[]);

const char hostname[];
const char username[];
const char passwd[];
const char ticket[];
const unsigned cartnumber;
const unsigned cutnumber;
const char user_agent[];
```

## Description

**RD\_DeleteAudio** is the function to use to delete PCM/MPEG data from the audio store.

**Table 1. RD\_DeleteAudio function call fields**

FIELD NAME	FIELD TYPE	MEANING	REMARKS
hostname	Character Array	Name Of Rivendell DB Host	Mandatory
username	Character Array	Rivendell User Name	Mandatory When NO Ticket Provided
passwd	Character Array	Rivendell User Password	Mandatory When NO Ticket Provided
ticket	Character Array	Rivendell Authentication Ticket	Mandatory When NO User/Password Pair Provided.
cartnumber	unsigned integer	Cart Number	Mandatory
cutnumber	unsigned integer	Cut Number	Mandatory
user_agent	Character Array	User Agent Value put into HTTP request	Optional (default is Rivendell-C-API/x.x.x)

## RETURN VALUE

On success, zero is returned.

If a server error occurs a -1 is returned. If a client error occurs a specific error number is returned.

## ERRORS

400 Missing Cart Number / Cut Number Error.

403 User Authentication Error.

404 No Such Cut or Invalid Permissions.

nnn Unknown Error Occurred.