
Name

rd_removecut — Rivendell Remove Cut C Library Function

Synopsis

```
#include <rivwebcapi/rd_removecut.h>

int RD_RemoveCut(hostname[], username[], passwd[], ticket[], cartnum-
ber, cutnumber, user_agent[]);

const char hostname[];
const char username[];
const char passwd[];
const char ticket[];
const unsigned cartnumber;
const unsigned cutnumber;
const char user_agent[];
```

Description

RD_RemoveCut is the function to use to remove a cut from the Rivendell database.

Table 1. RD_RemoveCut function call fields

FIELD NAME	FIELD TYPE	MEANING	REMARKS
hostname	Character Array	Name Of Rivendell DB Host	Mandatory
username	Character Array	Rivendell User Name	Mandatory When NO Ticket Provided
passwd	Character Array	Rivendell User Pass-word	Mandatory When NO Ticket Provided
ticket	Character Array	Rivendell Authentifica-tion Ticket	Mandatory When NO User/Password Pair Pro-vided.
cartnumber	unsigned integer	Cart Number	Mandatory
cutnumber	unsigned integer	Cut Number	Mandatory
user_agent	Character Array	User Agent Value put into HTTP request	Optional (default is Rivendell-C-API/x.x.x)

RETURN VALUE

On success, zero is returned.

If a server error occurs a -1 is returned. If a client error occurs a specific error number is returned.

ERRORS

400 Missing Cart Number / Cut Number Error.

403 User Authentication Error.

404 Unauthorized or No Such Cart/Cut.

nnn Unknown Error Occurred.